

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

FLEXSEAL 300

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Building and construction: hydroexpansive sealant

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

AZICHEM Srl

Street : Via G. Gentile16/A

Postal code/city : 46044 Goito (MN)

Telephone : +390376604185/604365

Telefax : +39 0376 604398

Information contact : info@azichem.com

1.4 Emergency telephone number

Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano) (24h)

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)

Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo)

Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze)

Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma)

Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma) Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Corrosion (GHS05) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

ALUMINIUM SULFATE ; CAS No. : 10043-01-3

HEXAMETHYLENE DISOCYANATE, OLIGOMERS ; CAS No. : 28182-81-2

Hazard statements

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P310	Immediately call a POISON CENTER/doctor
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water
Special rules for supplemental label elements for certain mixtures	
EUH204	Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

ALUMINIUM SULFATE ; REACH registration No. : 01-2119531538-36 ; EC No. : 233-135-0; CAS No. : 10043-01-3

Weight fraction : $\geq 25 - < 45$ %
Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318

OXYDIPROPYL DIBENZOATE ; REACH registration No. : 01-2119529241-49 ; EC No. : 248-258-5; CAS No. : 27138-31-4

Weight fraction : $\geq 10 - < 15$ %
Classification 1272/2008 [CLP] : Aquatic Chronic 3 ; H412

HEXAMETHYLENE DISOCYANATE, OLIGOMERS ; REACH registration No. : 01-2119488934-20 ; EC No. : 500-060-2; CAS No. : 28182-81-2

Weight fraction : $\geq 5 - < 10$ %
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H332 Skin Sens. 1 ; H317 STOT SE 3 ; H335

GAMMA-BUTYROLACTONE ; EC No. : 202-509-5; CAS No. : 96-48-0

Weight fraction : $\geq 0.5 - < 5$ %
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Eye Irrit. 2 ; H319

Additional information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove victim out of the danger area. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

In case of skin contact

Wash immediately with: Water Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician. In case of skin reactions, consult a physician.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

4.2 Most important symptoms and effects, both acute and delayed

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

May cause an allergic skin reaction. Risk of serious damage to eyes.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder alcohol resistant foam Carbon dioxide (CO₂) Water mist

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide Carbon dioxide (CO₂) Sulphur oxides Aluminum oxides.

5.3 Advice for firefighters

Remove persons to safety.

Special protective equipment for firefighters

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Clear spills immediately. Wear a self-contained breathing apparatus and chemical protective clothing.

For non-emergency personnel

Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

For cleaning up

The contaminated area should be cleaned up immediately with: Water Retain contaminated washing water and dispose it.

6.4 Reference to other sections

Reference to other sections Safe handling: see section 7 Personal protection equipment: see section 8

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Protective measures

Specific requirements or handling rules

Do not breathe dust. Do not breathe gas/fumes/vapour/spray. See section 8.

Advices on general occupational hygiene

Normal precautions taken when handling chemicals should be observed.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

7.2 Conditions for safe storage, including any incompatibilities

Only use containers specifically approved for the substance/product.

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect against UV-radiation/sunlight Humidity.

Hints on joint storage

Storage class : 13

Storage class (TRGS 510) : 11

Keep away from

Store at least 3 metres apart from: Chemicals/products that react together readily

Further information on storage conditions

Keep container tightly closed and in a well-ventilated place.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type :	DNEL Consumer (local) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route :	Dermal
Exposure frequency :	Short-term (acute)
Limit value :	4,6 mg/cm ²
Limit value type :	DNEL Consumer (local) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route :	Inhalation
Exposure frequency :	Short-term (acute)
Limit value :	5 mg/m ³
Limit value type :	DNEL Consumer (local) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	1,5 mg/m ³
Limit value type :	DNEL Consumer (local) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route :	Dermal
Exposure frequency :	Long-term (repeated)
Limit value :	9,2 mg/cm ²
Limit value type :	DNEL Consumer (systemic) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route :	Inhalation
Exposure frequency :	Short-term (acute)
Limit value :	5 mg/m ³
Limit value type :	DNEL Consumer (systemic) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route :	Oral
Exposure frequency :	Short-term (acute)
Limit value :	92,4 mg/kg
Limit value type :	DNEL Consumer (systemic) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route :	Dermal
Exposure frequency :	Long-term (repeated)
Limit value :	1,36 mg/kg
Limit value type :	DNEL Consumer (systemic) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route :	Inhalation
Exposure frequency :	Long-term (repeated)
Limit value :	1,5 mg/m ³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

Limit value type : DNEL Consumer (systemic) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Oral
Exposure frequency : Long-term (repeated)
Limit value : 54,4 mg/kg

Limit value type : DNEL Consumer (systemic) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Dermal
Exposure frequency : Short-term (acute)
Limit value : 233,5 mg/kg

Limit value type : DNEL worker (local) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Dermal
Exposure frequency : Short-term (acute)
Limit value : 476 mg/kg

Limit value type : DNEL worker (local) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Dermal
Exposure frequency : Short-term (acute)
Limit value : 9,2 mg/m³

Limit value type : DNEL worker (local) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 10 mg/m³

Limit value type : DNEL worker (local) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 9,2 mg/cm²

Limit value type : DNEL worker (local) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 3 mg/m³

Limit value type : DNEL worker (systemic) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 10 mg/m³

Limit value type : DNEL worker (systemic) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 2,72 mg/kg

Limit value type : DNEL worker (systemic) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 3 mg/m³

PNEC

Limit value type : PNEC aquatic, freshwater (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Limit value : 4,5 mg/l

Limit value type : PNEC aquatic, intermittent release (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Limit value : 30,11 mg/l

Limit value type : PNEC aquatic, marine water (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Limit value : 64 mg/l

Limit value type : PNEC sediment, freshwater (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Limit value : 10 mg/kg

Limit value type : PNEC sediment, marine water (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Limit value : 31,4 mg/kg

Limit value type : PNEC Soil (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Limit value : 58 mg/kg

Limit value type : PNEC Secondary Poisoning (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

Limit value : 150 mg/kg
Limit value type : PNEC sewage treatment plant (STP) (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Limit value : 60,2 mg/l

8.2 Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment



When using do not eat, drink, smoke, sniff.

Eye/face protection

Suitable eye protection

Safety glasses with side shields (EN 166).

Skin protection

Hand protection

Wear rubber gloves approved under standard EN374.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Full-/half-/quarter-face masks (DIN EN 136/140) Filter type: A

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Safety relevant basis data

Aspect			Pasta
Colour			red / brown
Odour			typical
Melting point/melting range :	(1013 hPa)		not determined
Vapour density	((air = 1))		Not Determined
Initial boiling point and boiling range :	(1013 hPa)		not determined
Decomposition temperature :			not determined
Flash point :	>		98 °C
Ignition temperature :			not determined
Flammability (solid, gas)			Data not available
Lower explosion limit :			not determined
Upper explosion limit :			not determined
Explosive properties			Not applicable
Vapour pressure	(20 °C)	approx.	0,27 hPa
Density :	(20 °C)		1,3 g/cm ³
Density :	(23 °C)		No data available
Water solubility :	(20 °C)		insoluble
pH :			not determined
Log Pow	(20 °C)		not applicable
Viscosity :	(20 °C)		not determined
Viscosity :	(23 °C)		No data available
Odour threshold :			not determined
Evaporation rate :			not determined

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

Maximum VOC content (EC) : = 0 Wt %
Oxidizing properties : Not oxidising

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage and handling conditions.

10.2 Chemical stability

Stable under recommended storage and handling conditions. See section 7. No additional measures necessary.

10.3 Possibility of hazardous reactions

Reacts with strong oxidants.

10.4 Conditions to avoid

None particular

10.5 Incompatible materials

May react violently with strong acids. Oxidizing agents.

10.6 Hazardous decomposition products

Carbon monoxide Sulphur oxides Carbon dioxide (CO₂) Aluminum oxides.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter :	LD50 (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Exposure route :	Oral
Species :	Mouse
Effective dose :	> 4618 mg/kg
Parameter :	LD50 (OXYDIPROPYL DIBENZOATE ; CAS No. : 27138-31-4)
Exposure route :	Oral
Species :	Rat
Effective dose :	= 5072 mg/kg
Parameter :	LD50 (HEXAMETHYLENE DISOCYANATE, OLIGOMERS ; CAS No. : 28182-81-2)
Exposure route :	Oral
Species :	Rat (female)
Effective dose :	> 2500 mg/kg

Acute dermal toxicity

Parameter :	LD50 (OXYDIPROPYL DIBENZOATE ; CAS No. : 27138-31-4)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (HEXAMETHYLENE DISOCYANATE, OLIGOMERS ; CAS No. : 28182-81-2)
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg

Acute inhalation toxicity

Parameter :	LC50 (OXYDIPROPYL DIBENZOATE ; CAS No. : 27138-31-4)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 200 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

Exposure time : 4 h

Irritant and corrosive effects

Primary irritation to the skin

Not an irritant.

Irritation to eyes

Risk of serious damage to eyes.

Irritation to respiratory tract

Not an irritant.

Sensitisation

In case of skin contact

sensitising.

In case of inhalation

not sensitising.

Repeated dose toxicity (subacute, subchronic, chronic)

There were no chronic effects or effects at low concentrations.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The ingredients in this mixture do not meet the criteria for classification as CMR according to CLP.

SECTION 12: Ecological information

Do not allow uncontrolled discharge of product into the environment.

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter :	LC50 (ALUMINIUM SULFATE ; CAS No. : 10043-01-3)
Species :	Pimephales promelas (fathead minnow)
Effective dose :	122,17 mg/l
Exposure time :	192 h
Parameter :	LC50 (OXYDIPROPYL DIBENZOATE ; CAS No. : 27138-31-4)
Species :	Oncorhynchus mykiss (Rainbow trout)
Effective dose :	0,25 mg/l
Exposure time :	96 h

Acute (short-term) daphnia toxicity

Parameter :	EC50 (OXYDIPROPYL DIBENZOATE ; CAS No. : 27138-31-4)
Species :	Daphnia magna (Big water flea)
Effective dose :	19,3 mg/l
Exposure time :	48 h
Parameter :	EC50 (HEXAMETHYLENE DISOCYANATE, OLIGOMERS ; CAS No. : 28182-81-2)
Species :	Daphnia magna (Big water flea)
Effective dose :	> 127 mg/l
Exposure time :	48 h

Acute (short-term) algae toxicity

Parameter :	EC50 (OXYDIPROPYL DIBENZOATE ; CAS No. : 27138-31-4)
Species :	Pseudokirchneriella subcapitata
Effective dose :	4,9 mg/l
Exposure time :	72 h
Parameter :	EC50 (HEXAMETHYLENE DISOCYANATE, OLIGOMERS ; CAS No. : 28182-81-2)
Species :	Desmodesmus subspicatus
Effective dose :	> 1000 mg/l
Exposure time :	72 h

12.2 Persistence and degradability

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

Biodegradation

Not readily biodegradable (according to OECD criteria).

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

There are no data available on the mixture itself.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Dispose according to legislation.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) 1907/2006 (REACH).

Regulation (EC) No 1272/2008 (CLP).

Regulation (EU) 2015/830 requirements for the compilation of safety data sheets.

Amendings, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008: Commission Regulation (EC) No 790/2009 (I ATP). Commission Regulation (EU) No 286/2011(II ATP). Commission Regulation (EU) No 618/2012 (III ATP). Commission Regulation (EU) No 487/2013 (IV ATP). Commission Regulation (EU) No 944/2013 (V ATP). Commission Regulation (EU) No 605/2014 (VI ATP). Commission Regulation (EU) No 1297/2014 (VII ATP). Commission Regulation (EU) No 2015/1221 (VIII ATP). Commission Regulation (EU) No

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

2016/1179 (IX ATP). Commission Regulation 2017/776 (EU) No (X ATP).

Other regulations (EU)

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]
This product is not classified according to Directive 2012/18/EU.

Regulation (CE) 1907/2006: Substance of very high concern included in the SVHC Candidate List

None

National regulations

Italy: Legislative Decree 81/2008 (Consolidated Law on protection of health and safety at work), as amended and Directive 2009/161/UE - chemical risk assessment in accordance with Title IX

Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP]

16.2 Abbreviations and acronyms

LEGENDA:

ADR:	Accord européen relative au transport international des marchandises dangereuses par route (accordo europeo relativo al trasporto internazionale delle merci pericolose su strada)
ASTM:	ASTM International, originariamente nota come American Society for Testing and Materials (ASTM)
EINECS:	European Inventory of Existing Commercial Chemical Substances (Registro Europeo delle Sostanze chimiche in Commercio)
EC(0/50/100):	Effective Concentration 0/50/100 (Concentrazione Effettiva Massima per 0/50/100% degli Individui)
LC(0/50/100):	Lethal Concentration 0/50/100 (Concentrazione Letale per 0/50/100% degli Individui)
IC50:	Inhibitor Concentration 50 (Concentrazione Inibente per il 50% degli Individui)
NOEL:	No Observed Effect Level (Dose massima senza effetti)
NOEC:	No Observed Effect Concentration (Concentrazione massima senza effetti)
LOEC:	Lowest Observed Effect Concentration (Concentrazione massima alla quale è possibile evidenziare un effetto)
DNEL:	Derived No Effect Level (Dose derivata di non effetto)
DMEL:	Derived Minimum Effect Level (Dose derivata di minimo effetto)
CLP:	Classification, Labelling and Packaging (Classificazione, Etichettatura e Imballaggio)
CSR:	Rapporto sulla Sicurezza Chimica (Chemical Safety Report)
LD(0/50/100):	Lethal Dose 0/50/100 (Dose Letale per 0/50/100% degli Individui)
IATA:	International Air Transport Association (Associazione Internazionale del Trasporto Aereo)
ICAO:	International Civil Aviation Organization (Organizzazione Internazionale dell'Aviazione Civile)
Codice IMDG:	International Maritime Dangerous Goods code (Codice sul Regolamento del Trasporto Marittimo)
PBT:	Persistent, bioaccumulative and toxic (sostanze persistenti bioaccumulabili e tossiche)
RID:	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regolamento concernente il trasporto Internazionale ferroviario delle merci Pericolose)
STEL:	Short term exposure limit (limite di esposizione a breve termine)
TLV:	Threshold limit value (soglia di valore limite)
TWA:	Time Weighted Average (media ponderata nel tempo)
UE:	Unione Europea
vPvB:	Very persistent very bioaccumulative (sostanze molto persistenti e molto bioaccumulabili)
N.D.:	Non disponibile.
N.A.:	Non applicabile
AwSV.:	Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV))

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : FLEXSEAL 300
Revision date : 31.08.2020
Print date : 31.08.2020

Version (Revision) : 3.0.0 (2.0.0)

PNEC: Predicted No Effect Concentration
PNOS: Particulates not Otherwise Specified
BOD: Biochemical Oxygen Demand
COD: Chemical Oxygen Demand
BCF: BioConcentration Factor
TRGS : Technische Regeln für Gefahrstoffe -Technical Rules for Hazardous Substances, defined by The Federal Institute for Occupational Safety and Health, Germany
LCLo: Lethal Concentration Low (La minima concentrazione letale)
ThOD: Theoretical Oxygen Demand

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

calculated.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
