# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: REPAR PLUG
Pavision date: 22.05.2017

**Revision date :** 22.05.2017 **Version (Revision) :** 2.0.0 (1.0.0)

**Print date :** 02.06.2017

#### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

REPAR PLUG

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Preparation for construction and construction: Super-adhesive rinse for cementitious or low absorbent substrates.

# 1.3 Details of the supplier of the safety data sheet

# Supplier (manufacturer/importer/only representative/downstream user/distributor)

AZICHEM Srl

Street: Via G. Gentile 16/A

**Postal code/city:** 46044 Goito (MN) **Telephone:** +390376604185/604365

**Telefax:** +39 0376 604398

**Information contact:** info@azichem.com

### 1.4 Emergency telephone number

Centro Antiveleni di Milano +39 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano) (24h)

Centro Antiveleni di Pavia +39 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)
Centro Antiveleni di Bergamo +39 800 883300 (CAV Ospedali Riuniti - Bergamo)
Centro Antiveleni di Firenze +39 055 7947819 (CAV Ospedale Careggi - Firenze)
Centro Antiveleni di Roma +39 06 3054343 (CAV Policlinico Gemelli - Roma)
Centro Antiveleni di Roma +39 06 49978000 (CAV Policlinico Umberto I - Roma)
Centro Antiveleni di Napoli +39 081 7472870 (CAV Ospedale Cardarelli - Napoli)

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Dam. 1; H318 - Serious eye damage/eye irritation: Category 1; Causes serious eye damage.

Skin Irrit. 2; H315 - Skin corrosion/irritation: Category 2; Causes skin irritation.

Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction. STOT SE 3; H335 - STOT-single exposure: Category 3; May cause respiratory irritation.

#### 2.2 Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

**Hazard pictograms** 





Corrosion (GHS05) · Exclamation mark (GHS07)

# Signal word

Danger

# Hazard components for labelling

CEMENT, PORTLAND, CHEMICALS; CAS No.: 65997-15-1

FLUE DUST; CAS No.: 68475-76-3

#### **Hazard statements**

H318 Causes serious eye damage. H315 Causes skin irritation.

Page: 1/9

(EN/D)

# according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** REPAR PLUG

**Revision date:** 22.05.2017 **Version (Revision):** 2.0.0 (1.0.0)

**Print date :** 02.06.2017

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

# **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P310 Immediately call a POISON CENTER/doctor

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

#### 2.3 Other hazards

None

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### **Hazardous ingredients**

CEMENT, PORTLAND, CHEMICALS; EC No.: 266-043-4; CAS No.: 65997-15-1

Weight fraction :  $\geq 40 - < 60 \%$ 

Classification 1272/2008 [CLP] : Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

FLUE DUST; REACH registration No.: 01-2119486767-17; EC No.: 270-659-9; CAS No.: 68475-76-3

Weight fraction :  $\geq 0.1 - < 0.5 \%$ 

Classification 1272/2008 [CLP] : Eye Dam. 1; H318 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335

Additional information

Full text of H- and EUH-statements: see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

When in doubt or if symptoms are observed, get medical advice.

#### Following inhalation

Remove victim out of the danger area. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

#### In case of skin contact

Wash immediately with: Water Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician. In case of skin reactions, consult a physician.

#### After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

### After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

#### 4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye damage. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

# 4.3 Indication of any immediate medical attention and special treatment needed

None

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

# Suitable extinguishing media

Extinguishing powder alcohol resistant foam Carbon dioxide (CO2) Water mist

### 5.2 Special hazards arising from the substance or mixture

Page: 2/9

# according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** REPAR PLUG

**Revision date:** 22.05.2017 **Version (Revision):** 2.0.0 (1.0.0)

**Print date :** 02.06.2017

None

#### 5.3 Advice for firefighters

Remove persons to safety.

### **Special protective equipment for firefighters**

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Clear spills immediately. Wear a self-contained breathing apparatus and chemical protective clothing.

#### For non-emergency personnel

Remove persons to safety.

#### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

#### For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

# For cleaning up

The contaminated area should be cleaned up immediately with: Water Retain contaminated washing water and dispose it.

# 6.4 Reference to other sections

Reference to other sections Safe handling: see section 7 Personal protection equipment: see section 8

# **SECTION 7: Handling and storage**



### 7.1 Precautions for safe handling

#### **Protective measures**

#### Specific requirements or handling rules

Do not breathe dust. Do not breathe gas/fumes/vapour/spray. See section 8.

### Advices on general occupational hygiene

Normal precautions taken when handling chemicals should be observed.

# 7.2 Conditions for safe storage, including any incompatibilities

Only use containers specifically approved for the substance/product.

### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect against UV-radiation/sunlight Humidity.

# Hints on joint storage

Storage class: 13

Storage class (TRGS 510): 13

**Keep away from** 

Store at least 3 metres apart from: Chemicals/products that react together readily

# Further information on storage conditions

Keep container tightly closed and in a well-ventilated place.

Page: 3 / 9

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: REPAR PLUG

**Revision date :** 22.05.2017 **Version (Revision) :** 2.0.0 (1.0.0)

**Print date :** 02.06.2017

#### 7.3 Specific end use(s)

None

### **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

### **DNEL/DMEL and PNEC values**

#### **DNEL/DMEL**

Limit value type : DNEL worker (local) ( CEMENT, PORTLAND, CHEMICALS ; CAS No. : 65997-15-1 )

Exposure route : Inhalation
Exposure frequency : Short-term (acute)

Limit value : 1 mg/m<sup>3</sup>

Limit value type: DNEL Consumer (local) (FLUE DUST; CAS No.: 68475-76-3)

Exposure route : Inhalation
Exposure frequency : Short-term (acute)

Limit value : 1 mg/m<sup>3</sup>

Limit value type : DNEL Consumer (local) ( FLUE DUST ; CAS No. : 68475-76-3 )

Exposure route: Inhalation

Exposure frequency: Long-term (repeated)

Limit value: 4 mg/m<sup>3</sup>

Limit value type : DNEL worker (local) ( FLUE DUST ; CAS No. : 68475-76-3 )

Exposure route: Inhalation

Exposure frequency: Long-term (repeated)

Limit value: 1 mg/m<sup>3</sup>

Limit value type : DNEL worker (local) ( FLUE DUST ; CAS No. : 68475-76-3 )

Exposure route: Inhalation
Exposure frequency: Short-term (acute)

Limit value : 4 mg/m<sup>3</sup>

**PNEC** 

Limit value type: PNEC aquatic, freshwater (FLUE DUST; CAS No.: 68475-76-3)

Limit value : 28 mg/m<sup>3</sup>

Limit value type : PNEC aquatic, intermittent release ( FLUE DUST ; CAS No. : 68475-76-3 )

Limit value : 282 mg/m<sup>3</sup>

Limit value type: PNEC aquatic, marine water (FLUE DUST; CAS No.: 68475-76-3)

Limit value : 3 mg/m<sup>3</sup>

Limit value : 0,875 mg/kg

Limit value type : PNEC sediment, marine water ( FLUE DUST ; CAS No. : 68475-76-3 )

Limit value : 0,088 mg/kg

Limit value type : PNEC soil, freshwater ( FLUE DUST ; CAS No. : 68475-76-3 )

Limit value : 5 mg/kg

Limit value type : PNEC sewage treatment plant (STP) ( FLUE DUST ; CAS No. : 68475-76-3 )

Limit value : 6 mg/

# 8.2 Exposure controls

#### **Appropriate engineering controls**

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### **Personal protection equipment**

Page: 4 / 9

# according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** REPAR PLUG **Revision date :** 22.05.2017

 Revision date :
 22.05.2017
 Version (Revision) :
 2.0.0 (1.0.0)

 Print date :
 02.06.2017







When using do not eat, drink, smoke, sniff.

### **Eye/face protection**

Suitable eye protection

Eye glasses with side protection

#### Skin protection

**Hand protection** 

Tested protective gloves must be worn

#### Respiratory protection

Quarter-face mask (DIN EN 140) Half-face mask (DIN EN 140) Filtering Half-face mask (DIN EN 149)

#### **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties Safety relevant basis data

Aspect powder Colour Light brown Odour none (1013 hPa) Melting point/melting range: No data available Vapour density ((air = 1))Data not available Initial boiling point and boiling range: (1013 hPa) No data available **Decomposition temperature:** No data available **Self flammability** No data available Flash point: Not flammable Data not available Flammability (solid, gas) Lower explosion limit: No data available Upper explosion limit: No data available **Explosive properties** Data not available ( 20 °C ) Vapour pressure No data available Density: (20°C) No data available Water solubility: (20°C) Almost insoluble pH: 11 **Log Pow** (20°C) not applicable Viscosity: ( 20 °C ) No data available **Odour threshold** Data not available **Evaporation rate** Data not available Maximum VOC content (EC): Wt % Oxidizing properties Not oxidising

# 9.2 Other information

None

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No information available.

#### 10.2 Chemical stability

See section 7. No additional measures necessary.

### 10.3 Possibility of hazardous reactions

No information available.

Page: 5 / 9

(EN/D)

# according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** REPAR PLUG

**Revision date :** 22.05.2017 **Version (Revision) :** 2.0.0 (1.0.0)

**Print date :** 02.06.2017

#### 10.4 Conditions to avoid

No information available.

#### 10.5 Incompatible materials

No information available.

#### 10.6 Hazardous decomposition products

No information available.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

#### **Acute effects**

#### **Acute oral toxicity**

Parameter: LD50 (FLUE DUST; CAS No.: 68475-76-3)

Exposure route : Oral Species : Rat

Effective dose : > 1848 mg/kg bw/day

Exposure time: 7 days

Acute dermal toxicity

Parameter: LD50 ( CEMENT, PORTLAND, CHEMICALS ; CAS No. : 65997-15-1 )

Exposure route: Dermal Species: Rabbit

Effective dose : > 2000 mg/kg bw/day

Exposure time: 24 days

Parameter: LD50 (FLUE DUST; CAS No.: 68475-76-3)

Exposure route : Dermal Species : Rat

Effective dose : > 2000 mg/kg bw/day

Acute inhalation toxicity

Parameter: LD50 (FLUE DUST; CAS No.: 68475-76-3)

Exposure route: Inhalation
Species: Rat
Effective dose: > 6,04 mg/l
Exposure time: 4 h

#### **Irritant and corrosive effects**

#### Primary irritation to the skin

Irritant.

# Irritation to eyes

Causes serious eye damage.

#### Irritation to respiratory tract

Irritant.

#### **Sensitisation**

May cause an allergic skin reaction.

#### Repeated dose toxicity (subacute, subchronic, chronic)

There were no chronic effects or effects at low concentrations.

# CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The ingredients in this mixture do not meet the criteria for classification as CMR according to CLP.

# **SECTION 12: Ecological information**

Do not allow uncontrolled discharge of product into the environment.

Page: 6 / 9

# according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** REPAR PLUG

**Revision date :** 22.05.2017 **Version (Revision) :** 2.0.0 (1.0.0)

**Print date :** 02.06.2017

#### 12.1 Toxicity

No information available.

#### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

No information available.

#### 12.6 Other adverse effects

No information available.

### 12.7 Additional ecotoxicological information

None

### **SECTION 13: Disposal considerations**

# 13.1 Waste treatment methods

### **Product/Packaging disposal**

Dispose according to legislation.

### **SECTION 14: Transport information**

#### 14.1 UN number

No dangerous good in sense of these transport regulations.

#### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

# 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

#### 14.4 Packing group

No dangerous good in sense of these transport regulations.

# 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

#### 14.6 Special precautions for user

None

# 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU** legislation

Regulation (EC) 1907/2006/CE (REACh). Regulation (EC) No 1272/2008 (CLP). Regulation (EU) 2015/830 requirements for the compilation of safety data sheets. Commission Regulation (EC) No 790/2009/CE (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 286/2011 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 618/2012 (amending, for the purposes of its adaptation to technical

Page: 7 / 9

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR PLUG

**Revision date :** 22.05.2017 **Version (Revision) :** 2.0.0 (1.0.0)

**Print date :** 02.06.2017

and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 487/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 758/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 944/2013 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 605/2014 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008). Commission Regulation (EU) No 1297/2015 (amending, for the purposes of its adaptation to technical and scientific progress (ATP), Regulation (EC) No 1272/2008).

#### Other regulations (EU)

Regulation (CE) 1907/2006: Substance of very high concern included in the SVHC Candidate List None

#### **National regulations**

Italy: Legislative Decree 81/2008 (Consolidated Law on protection of health and safety at work), as amended and Directive 2009/161/UE - chemical risk assessment in accordance with Title IX

#### Water hazard class (WGK)

Class: nwg (Non-hazardous to water) Classification according to VwVwS

#### 15.2 Chemical safety assessment

not applicable

### **SECTION 16: Other information**

#### 16.1 Indication of changes

None

### 16.2 Abbreviations and acronyms

#### **LEGENDA:**

ADR: Accord européen relative au transport international des marchandises dangereuses par route (accordo

europeo relativo al trasporto internazionale delle merci pericolose su strada)

ASTM: ASTM International, originariamente nota come American Society for Testing and Materials (ASTM)

EINECS: European Inventory of Existing Commercial Chemical Substances (Registro Europeo delle Sostanze

chimiche in Commercio)

EC(0/50/100): Effective Concentration 0/50/100 (Concentrazione Effettiva Massima per 0/50100% degli Individui)

LC(0/50/100): Lethal Concentration 0/50/100 (Concentrazione Letale per 0/50100% degli Individui)

IC50: Inhibitor Concentration 50 (Concentrazione Inibente per il 50% degli Individui)

NOEL: No Observed Effect Level (Dose massima senza effetti)

NOEC: No Observed Effect Concentration (Concentrazione massima senza effetti)

LOEC: Lowest Observed Effect Concentration (Concentrazione massima alla quale è possibile evidenziare un

effetto)

DNEL: Derived No Effect Level (Dose derivata di non effetto)

DMEL: Derived Minimum Effect Level (Dose derivata di minimo effetto)

CLP: Classification, Labelling and Packaging (Classificazione, Etichettatura e Imballaggio)

CSR: Rapporto sulla Sicurezza Chimica (Chemical Safety Report)
LD(0/50/100): Lethal Dose 0/50/100 (Dose Letale per 0/50/100% degli Individui)

IATA: International Air Transport Association (Associazione Internazionale del Trasporto Aereo)
ICAO: International Civil Aviation Organizzation (Organizzazione Internazionale dell'Aviazione Civile)
Codice IMDG: International Maritime Dangerous Goods code (Codice sul Regolamento del Trasporto Marittimo)

PBT: Persistent, bioaccumulative and toxic (sostanze persistenti bioaccumulabili e tossiche)

RID: Règlement concernent le transport International ferroviaire des marchandises Dangereuses (Regolamento concernente il trasporto Internazionale ferroviario delle merci Pericolose)

STEL: Short term exposure limit (limite di esposizione a breve termine)

TLV: Threshold limit value (soglia di valore limite)

TWA: Time Weighted Average (media ponderata nel tempo)

UE: Unione Europea

vPvB: Very persistent very bioaccumulative (sostanze molto persistenti e molto bioaccumulabili)

N.D.: Non disponibile.

Page: 8 / 9

# according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : REPAR PLUG

**Revision date:** 22.05.2017 **Version (Revision):** 2.0.0 (1.0.0)

**Print date :** 02.06.2017

N.A.: Non applicabile

VwVwS.: Text of Administrative Regulation on the Classification of Substances hazardous to waters into Water

Hazard Classes (Verwaltungsvorschrift wassergefährdende Stoffe – VwVwS)

PNEC: Predicted No Effect Concentration
PNOS: Particulates not Otherwise Specified
BOD: Biochemical Oxygen Demand
COD: Chemical Oxygen Demand
BCF: BioConcentration Factor

TRGS: Technische Regeln für Gefahrstoffe -Technical Rules for Hazardous Substances, defined by The

Federal Institute for Occupational Safety and Health, Germany

LCLo: Lethal Concentration Low (La minima concentrazione letale)

ThOD: Theoretical Oxygen Demand

# 16.3 Key literature references and sources for data

None

# 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

calculated.

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

#### 16.6 Training advice

None

#### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 9 / 9